

Hydraulic internal vibrator

Orders

Hotline

Chat zalo

Whatsapp

Facebook

Specification:

MODEL	MP 315	MP 215	MP 235 EDGER
Power: Honda	GX690 - Cooled Gas (688cc)	GX690 - Cooled Gas (688cc)	GX690 -Cooled Gas (688cc)
dimention	249 x 127 x 135 cm	198 x 104 x 135 cm	218 x 99 x 135 cm
Working width	95 in. (241 cm)	74 in. (188 cm)	85 in. (216 cm)
Plade diameter	46 in. (1,168 mm) 4-plade	36 in. (914 mm) 4-plade	36 in. (914 mm) pladea
Rotor speed	145 R/M	145 R/M	145 R/M
weight	830 lbs. (376 kg)	735 lbs. (333 kg)	783 lbs. (355 kg)
Fuel capacity	6 gal (23 L)	6 gal (23 L)	6 gal (23 L)

Diameter 2-5/8” (66.67mm)

Centrifugal force -1902lbs. (8460.51N)

Amplitute- 0.126” (3.20mm)

Effect diameter-26.50”-30.50” (673.1mm-774.7mm)

Oil flow 4GPM (15.14l/min)

Working pressure - 800-1300PSI (5.51-8.96MPa)

Back pressure- 150PSI (1.03MPa)

Related Products



Slipform Cement Spreader



Canal cylinder finisher VF450 SL



Cold matit paverment



Concrete cylinder finisher CF1250H



Concrete cylinder finisher CF1250E



Roller Screed