



Auger Torque Earth Drill excavator

[Orders](#)

[Hotline](#)

[Chat zalo](#)

[Whatsapp](#)

[Facebook](#)

In Which Cases Is Pre-Drilling Required Before Pile Pressing?

Based on many years of experience in concrete pile pressing and foundation construction, we have found that pre-drilling is required in the following situations:

- **When encountering hard soil or rock layers with high SPT values.** Specifically, clay with **SPT N30 > 8** or sand with **SPT N30 > 15**, where the pressure applied beneath the pile toe is insufficient to penetrate the layer. In such cases, pre-drilling is necessary to enable the pile to reach the designed tip elevation.
- **When the soil profile is non-uniform and contains hard lenses with high SPT values.** Pre-drilling through these hard layers helps ensure that the pile reaches the required design depth and tip elevation.
- **To allow the pile toe to bear on a stable soil or rock layer.** This improves pile stability and prevents sliding when constructing foundations in hilly or mountainous areas.
- **To prevent false refusal during pile pressing** when working in sandy soil conditions.
- **To minimize soil heave and reduce the risk of affecting adjacent structures,** especially when construction is carried out in densely populated urban areas.

Related Products



—

[Log Splitter](#)



—

[Cement Mixer Bowls](#)



—

[Skid steer loader pallet forks](#)



—

[Auger Torque Hydraulic Earth Auger for Truck-Mounted Cranes](#)



—

[Auger Torque Hydraulic Earth Drill Attachment for Excavators](#)



—

[Road Milling Machine Spare Parts](#)