

Concrete cylinder finisher CF1250H

Orders

Hotline

Chat zalo

Whatsapp

Facebook

The Concrete Cylinder Finisher CF1250 - Hydraulic is a perfect chosen for for concrete road paving as well as floors construction, Bridges surface, Airports, Sloop paving etc.

TECHNICAL SPECIFICATIONS

- Productivity : 150 square meter/ hour with single drum; 300 square meter/ hour with double drum.
- Paving width standard 2,5m – 6m. Can be paving up to 20m width with adding frame.
- modular frame made from welded steel panels, quickly install, be sure strong enough and easy transportation.
- finishing width is infinitely adjustable to within 1,25 meter less than the overall width. Finishing width adjustment are made from the operators control panel using automatic reverse controls
- four grade jacks, manually height adjustable
- four pairs of double flange wheels, 80 mm wide, by 140 mm diameter. Two pairs are hydraulically driven and two pairs are idle
- 250 mm diameter augers, for finishing carriage. One left hand, one right hand, with guard
- finishing cylinder mounted on finishing carriage, 250 mm diameter by 1250 mm long
- double chain undercarriage drive
- double rail/double wheel undercarriage guide
- designed for operation on flat and inclined surfaces without modification to basic frame structure.

-

- 
CÔNG TY TNHH
CƠ KHÍ VÀ XÂY LẮP
THỦ ĐỨC
- 
CÔNG TY TNHH
CƠ KHÍ VÀ XÂY LẮP
THỦ ĐỨC


CÔNG TY TNHH
CƠ KHÍ VÀ XÂY LẮP
THỦ ĐỨC

- 
CÔNG TY TNHH
THỦ ĐỨC

Related Products



Slipform Cement Spreader



Canal cylinder finisher VF450 SL



Cold matit paverment



Concrete cylinder finisher CF1250E



Roller Screed



Btxm construction hand tool